



Datasheet T072F

Articlenumber 1003293

Halfbridge Transducer with 73.75 mm/Vmm sensitivity and ± 1 mm measuring stroke, Pretravel adjustable. Spring push. Cable 2 m, cable exit radial.



Total Stroke, Measuring stroke, Pretravel, Pretravel default setting, Bearing, Lifetime, Tip rotation, Temperatur range, Mounting position, Tip, Bellow, Body diameter, Plug, Cable feature, Cable information

Total Stroke	2.2 mm
Measuring stroke	± 1.0 mm
Pretravel	adjustable
Pretravel default setting	- 1.1 mm
Bearing	Ball bearing, no side-play
Lifetime	> 10 Mio. Cycles
Tip rotation	1° over full stroke
Temperatur range	-10 to +65 °C, storage and operation
Mounting position	any
Tip	3 mm tungsten carbide ball, M2.5 fixing thread, exchangeable
Bellow	FPM / FKM
Body diameter	8h6
Plug	5 pin, 240°
Cable feature	PUR shielded, Length 2 m
Cable information	Outer- \varnothing 4.0 mm, drag chain compatible





Datasheet T072F

Articlenumber 1003293



Advance, Lift off, Spring rate, Spring rate information

Advance	spring push
Lift off	no
Spring rate	0.63 N
Spring rate information	at electrical zero, tolerance $\pm 20\%$

Repeatability, Linearity error

Repeatability	0.01 μm
Linearity error	0.6% FS (full-scale) $\pm 1000 \mu\text{m}$ range (at 20 °C $\pm 1^\circ\text{C}$)

Sensitivity, Setting, Amplifier input load, Drive frequency, Supply voltage, Coil scheme

Sensitivity	73.75 mV/(Vmm)
Setting	1:1
Amplifier input load	2 kOhm Input resistance, $\pm 0.1\%$
Drive frequency	13.0 kHz $\pm 5\%$
Supply voltage	3.0 V $\pm 0.5\%$ RMS
Coil scheme	Halfbridge, TESA® compatible

Documents information

Documents information	All drawings and 3D models are shown in "electrical zero" position.
-----------------------	---------------------------------------------------------------------

